

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended):      Network-unit for use in a telecommunication network and comprising

at least one input for receiving a signal comprising a first field which is directly analysable and a second field which is analysable after a processing,

a first analyser coupled to said at least one input for analysing first information originating from said first field,

a processor for performing said processing of second information originating from said second field, and

a second analyser coupled to said processor for analysing processed second information,

at least one output for sending a further signal to a further network-unit and comprising a third field which is directly analysable and a fourth field which is analysable after a processing in said further network-unit,

wherein said first analyser is coupled to said processor for, in dependence of an analysis result of said first information, ~~at least~~ selecting at least one output and switching at least a part of said signal to said selected output or performing said processing, with said first information

comprising non-address information, and with said second information comprising address information defining further network-units.

2. (original): Network-unit according to claim 1, wherein the network-unit further comprises

a first generator coupled to said at least one output for generating said third information, and

a second generator coupled to said at least one output for generating said fourth information.

3. (previously presented): Network-unit according to claim 1, wherein said first field comprises a quality field for indicating a quality, with said second field comprising an IP-address field for indicating an IP-address.

4. (previously presented): Network-unit according to claim 1, wherein said processing corresponds with defragmentation, decompression, demultiplexing and/or table consultation.

5. (currently amended): Telecommunication network comprising several network-units, at least a first network-unit comprising

at least one input for receiving a signal comprising a first field which is directly analysable and a second field which is analysable after a processing,

a first analyser coupled to said at least one input for analysing first information originating from said first field,

a processor for performing said processing of second information originating from said second field, and

a second analyser coupled to said processor for analysing processed second information, at least one output for sending a further signal to a second network-unit and comprising a third field which is directly analysable and a fourth field which is analysable after a processing in said second network-unit,

wherein said first analyser is coupled to said processor for, in dependence of an analysis result of said first information, ~~at least~~ selecting at least one output and switching at least a part of said signal to said selected output or performing said processing, with said first information comprising non-address information, and with said second information comprising address information defining said second network-unit.

6. (original): Telecommunication network according to claim 5, wherein the first network-unit further comprises

a first generator coupled to said at least one output for generating said third information, and

a second generator coupled to said at least one output for generating said fourth information.

7. (currently amended): Method for dealing with signals and comprising the steps of

receiving a signal comprising a first field which is directly analysable and a second field which is analysable after a processing,

analysing first information originating from said first field,

performing said processing of second information originating from said second field, and

analysing processed second information,

sending a further signal to a further network-unit and comprising a third field which is directly analysable and a fourth field which is analysable after a processing in said further network-unit,

wherein said method comprises the steps of, in dependence of an analysis result of said first information, ~~at least~~ selecting at least one output and switching at least a part of said signal to said selected output or performing said processing, with said first information comprising non-address information, and with said second information comprising address information defining further network-units.

8. (original): Method according to claim 7, wherein the method comprises the steps of  
generating said third information, and  
generating said fourth information.

9. (previously presented): Method according to claim 7, wherein said first field comprises a quality field for indicating a quality, with said second field comprising an IP-address field for indicating an IP-address.

10. (previously presented): Method according to claim 7, wherein said processing corresponds with defragmentation, decompression, demultiplexing and/or table consultation.

11. (new): The network-unit according to claim 1, wherein said first field comprises a layer 2 header and wherein said second field comprises a layer 3 header.

12. (new): The network-unit according to claim 1, wherein said first field comprises a plurality of subfields, wherein one of the plurality of subfields comprises the first information.

13. (new): The network-unit according to claim 1, wherein said first field is the first occurring field among a plurality of fields of a packet of the signal.